



MACHINE MODEL	HB1	HB5	HB10	HB20	HB50	HB1C	HB3C	HB6C	HB1K	HB3K	HB5K	HB10K
NOMINAL WEIGHT CAPACITY (Kg)	1	5	10	20	50	100	300	650	1000	3000	5000	10000
OVER LOAD PERMITTED UP TO (Kg)	2	8	15	30	75	200	450	1000	1800	4000	7500	12500
MAXIMUM DIAMETER OF ROTOR (mm)	150	180	250	500	700	900	1150	1350	1500	2100	2500	3000
MAXIMUM LENGTH OF BED (mm)												
BED SIZE - S	250	300	400	500	600	600	600	1200	2400	2400	2400	3600
BED SIZE - M	-	-	-	800	1000	1200	1600	2300	3800	3600	3600	7200
BED SIZE - L	-	-	-	1100	1600	1800	2300	3000	4800	4800	4800	10800
MINIMUM DISTANCE BETWEEN PEDESTALS (mm)	10	16	20	40	50	60	60	65	70	100	125	200
JOURNAL DIAMETER RANGE (mm)	2-15	3-20	5-25	8-50	8-60	10-80	12-100	15-120	15-140	25-180	25-250	40-300
MIN. RESIDUAL UNBALANCE (mmg)	0.1	0.1	0.2	0.25	0.5	0.75	0.75	1.0	2.0	5.0	7.5	10.0

Machine Confirm to ISO 2953 Balances to ISO 1940 Requirements



Precibalance Dynamic Balancing Machines Pvt Ltd

B-52, Sipcot Industrial Estate, Irunkattukottai

Sriperumpudur, India - 602105.

Ph. No : +91 9789055141 / 142

Fax No : +91

Website : [www.precibalance.com](http://www.precibalance.com)

email : [sales@precibalance.com](mailto:sales@precibalance.com)